



## LED eb Tubes



On Time Lighting's eb Tubes are commercial grade LED T8 lamps, perfect for illuminating and enhancing industrial buildings and commercial environments. The bulb is conveniently designed for easy install, without any rewiring.

### Features and Benefits

- No rewiring needed
- Works with fluorescent electronic ballast\* (Instant Start and Programmed Start)
- Long life
- High CRI
- Instant on, no delay
- Convenient and quick installation
- Utilizes existing instant start or rapid start sockets
- Compatible with controls and sensors
- Works in cold temperature applications
- Glass tube for superior optical performance
- 5 Year Warranty

### Application


- Warehouse
- Industrial
- Manufacturing facilities
- Commercial buildings
- Parking garages
- Office buildings

### Certifications



Made in the USA

### Specifications

MODEL#	LENGTH	LAMP WATTAGE	SYSTEM WATTAGE	CCT	LUMENS	CRI	BEAM ANGLE	LAMP EFFICACY	LIFE	
EB/L96T8/42W/840	96"	40W	42W	4000K	4200	83	325°	135	50,000	
EB/L48T8/12W/850	48"	12W	14W	5000K	1800	83	325°	135	50,000	Yes
EB/L48T8/12W/840	48"	12W	14W	4000K	1800	83	325°	135	50,000	Yes
EB/L48T8/12W/835	48"	12W	14W	3500K	1800	83	325°	135	50,000	Yes
EB/L36T8/10W/850	36"	10W	13W	5000K	1400	83	325°	135	50,000	
EB/L36T8/10W/840	36"	10W	13W	4000K	1400	83	325°	135	50,000	
EB/L36T8/10W/835	36"	10W	13W	3500K	1400	83	325°	135	50,000	
EB/L24T8/8W/850	24"	8W	11W	5000K	1100	83	325°	135	50,000	Yes
EB/L24T8/8W/840	24"	8W	11W	4000K	1100	83	325°	135	50,000	Yes

EB/L24T8/8W/835	24"	8W	11W	3500K	1100	83	325°	135	50,000	Yes
-----------------	-----	----	-----	-------	------	----	------	-----	--------	-----

## System Performance

**Model #: EB/L48T8/12W/8XX**

**Model #: EB/L24T8/8W/8XX**

SPECIFICATION	LOW BALLAST FACTOR (0.77)	NORMAL BALLAST FACTOR (0.88)	HIGH BALLAST FACTOR (1.18)
Lamp Wattage	10W	12W	16W
System Wattage	12W	14W	18W
Lumen Output	1380 lm	1800 lm	2200 lm
Lamp Efficacy (lm/W)	135 lm/W	135 lm/W	135 lm/W

SPECIFICATION	LOW BALLAST FACTOR (0.77)	NORMAL BALLAST FACTOR (0.88)	HIGH BALLAST FACTOR (1.18)
Lamp Wattage	7W	8W	10W
System Wattage	10W	11W	13W
Lumen Output	945 lm	1100 lm	1350 lm
Lamp Efficacy (lm/W)	135 lm/W	135 lm/W	135 lm/W

\* Please refer to "Ballast Compatibility List" on [ontimelighting.com](http://ontimelighting.com) for a list of ballasts compatible with this lamp.

**OnTimeLighting.com | 215.245.3400**  
**47B Runway Road, Levittown, PA 19057**