



Recessed Troffer Standard Lens



The RT-SL offers the look and feel of a fluorescent luminaire - subtle soft direct elements, interest and depth across the ceiling plane - with a contemporary look that blends with today's commercial spaces. The extruded acrylic lens with softening overlay provides a diffused luminance, with the effective combination of excellent light transmission and haze.

Features and Benefits

- High performance optical engine delivers main beam focus through the optically designed acrylic lens
- Linear ribbed acrylic lens with Lumieofi overlay manages the balance of efficiency and aesthetics
- Linear arrayed LED modules provide diffuse, but effective illumination
- LED light engine (optional) by Osram Sylvania, Philips, and others
- LED drivers deliver dimming capability

Application

- Recessed commercial applications
- Offices
- Hospitals
- Schools
- Standard 15/16" inverted T-Bar grid ceilings

Certifications



Made in the USA

Specifications

MODEL#	DIMENSIONS (FT)	WATTAGE	EFFICACY	CRI	CCT	LIFE	WARRANTY	VOLTAGE	UL	DLC
RT14-SL-2035	1x4	20	92.8	84.7	3500	50,000	5 Years	120-277V	X	
RT14-SL-4040	1x4	40	92.8	84.7	4000	50,000	5 Years	120-277V	X	
RT22-SL-4030	2x2	39.32	87.3	84.1	3089	50,000	5 Years	120-277V	X	X
RT22-SL-4035	2x2	39.32	87.3	84.1	3500	50,000	5 Years	120-277V	X	X
RT22-SL-4040	2x2	39.32	87.3	84.1	4000	50,000	5 Years	120-277V	X	X
RT22-SL-4050	2x2	39.32	87.3	84.1	4050	50,000	5 Years	120-277V	X	X
RT24-SL-42-840	2x4	39.29	103.6	82.6	4082	50,000	5 Years	120-277V	X	X
RT24-SL-30-840	2x4	29.8	102.6	82.6	4068	50,000	5 Years	120-277V	X	X
RT24-SL-5535	2x4	51.7	102.5	84.7	3579	50,000	5 Years	120-277V	X	X
RT24-SL-5540	2x4	51.7	102.5	84.7	4000	50,000	5 Years	120-277V	X	X