



## Recessed Troffer Curved Volumetric Lens



The RT-CL offers the look and feel of a fluorescent luminaire - subtle soft direct elements, interest and depth across the ceiling plane - with a contemporary look that blends with today's commercial spaces. The extruded acrylic lens with softening overlay provides a diffused luminance, with the effective combination of excellent light transmission and haze.

### Key Features and Benefits

- High performance optical engine delivers main beam focus through the optically designed acrylic lens
- Linear ribbed acrylic lens with Lumieofi overlay manages the balance of efficiency and aesthetics
- Linear arrayed LED modules provide diffuse, but effective illumination
- LED light engine (optional) by Osram Sylvania, Philips, and others
- LED drivers deliver dimming capability

### Application

- Recessed commercial applications
- Offices
- Hospitals
- Schools
- Standard 15/16" inverted T-Bar grid ceilings

### Certifications



Made in the USA

### Specifications

MODEL#	DIMENSIONS (FT)	WATTAGE	EFFICACY	CRI	CCT	LIFE	WARRANTY	VOLTAGE	UL	DLC
RT22-CL-4030	2x2	39.02	89.3	84.2	3084	50,000	5 Years	120-277V	X	X
RT22-CL-4035	2x2	39.02	89.3	84.2	3500	50,000	5 Years	120-277V	X	X
RT22-CL-4040	2x2	39.02	89.3	84.2	4000	50,000	5 Years	120-277V	X	X
RT22-CL-4050	2x2	39.02	89.3	84.2	5000	50,000	5 Years	120-277V	X	X
RT24-CL-7230	2x4	39.32	87.3	84.1	3084	50,000	5 Years	120-277V	X	X
RT24-CL-7235	2x4	39.32	87.3	84.1	3500	50,000	5 Years	120-277V	X	X
RT24-CL-7240	2x4	39.32	87.3	84.1	4000	50,000	5 Years	120-277V	X	X
RT24-CL-7250	2x4	39.32	87.3	84.1	5000	50,000	5 Years	120-277V	X	X