



## Recessed Indirect Troffer LED Fixture Series



The RI-TL offers the look and feel of a fluorescent luminaire □ subtle soft direct elements, interest and depth across the ceiling plane □ with a contemporary look that blends with today's commercial spaces. The extruded acrylic lens with softening overlay provides a diffused luminance, with the effective combination of excellent light transmission and haze.

### Features and Benefits

- **Decorative, glare reducing design** - Looks great in the ceiling and fixture flare is minimized.
- **Light Source** - LED light engine includes 50 chip board and matched driver from LG Innotek, Osram Sylvania, and Philips.
- **Low total harmonic distortion (THD)** - Decreased interference with infrared remote controlled electronics and other electronic appliances.
- **High Color Rendering Index** - Excellent and accurate color rendering.
- **Advanced computer designed specular reflector** - Extremely precise light focusing and distribution.
- **Wide variety of reflector, lens, and tube guard options** - Choose the lumen output and energy performance that's best for you, the customer, and the application. Use one fixture for consistent look and easier maintenance.
- **Extremely low lumen depreciation over lamp life** - Very infrequent lamp changes.

### Application

- Recessed commercial applications
- Offices
- Hospitals
- Schools
- Standard 15/16□ inverted T-Bar grid ceilings

### Certifications



Made in the USA

### Ordering Information

| Model          | Dimensions | Input Wattage | Efficacy( LpW) | Color Rendering Index(CRI) | Color Temperature(CCT) | Rated Life(L70) | Warranty | Voltage  | UL | DLC |
|----------------|------------|---------------|----------------|----------------------------|------------------------|-----------------|----------|----------|----|-----|
| RT22-RITL-2535 | 2x2        | 25            | 95             | 84.3                       | 3500                   | 50,000          | 5 Years  | 120-277V | X  |     |
| RT22-RITL-3540 | 2x2        | 35            | 95             | 84.3                       | 4000                   | 50,000          | 5 Years  | 120-277V | X  |     |
| RT24-RITL-3535 | 2x4        | 35            | 95             | 84.3                       | 3500                   | 50,000          | 5 Years  | 120-277V | X  |     |
| RT24-RITL-4540 | 2x4        | 45            | 95             | 84.3                       | 4000                   | 50,000          | 5 Years  | 120-277V | X  |     |