



## Recessed Troffer Central Basket LED



The RT-DL offers the look and feel of a fluorescent luminaire □ subtle soft direct elements, interest and depth across the ceiling plane □ with a contemporary look that blends with today's commercial spaces. The extruded acrylic lens with softening overlay provides a diffused luminance, with the effective combination of excellent light transmission and haze.

### Features and Benefits

- High performance optical engine delivers main beam focus through the optically designed acrylic lens
- Linear ribbed acrylic lens with Lumieofi overlay manages the balance of efficiency and aesthetics
- Linear arrayed LED modules provide diffuse, but effective illumination
- LED light engine (optional) by Osram Sylvania, Philips, and others
- LED drivers deliver dimming capability

### Application

- Recessed commercial applications
- Offices
- Hospitals
- Schools
- Standard 15/16□ inverted T-Bar grid ceilings

### Certifications



Made in the USA

### Ordering Information

MODEL #	DIMENSION (FT)	WATTAGE	EFFICACY	CRI	CCT	LIFE	WARRANTY	VOLTAGE	UL	DLC
RT22-DL-2535	2x2	25	95	84.2	3500	50,000	5 Years	120-277V	X	
RT22-DL-3540	2x2	20	95	84.2	4000	50,000	5 Years	120-277V	X	
RT24-DL-3535	2x4	35	95	84.4	3500	50,000	5 Years	120-277V	X	
RT24-DL-4540	2x4	45	95	84.4	4000	50,000	5 Years	120-277V	X	

OnTimeLighting.com | 215.245.3400  
47B Runway Road, Levittown, PA 19057