



LED DVPE Series Dust and Vapor Proof Fixture



On Time Lighting's LED Dust and Vapor Proof (DVPE) fixture series is an excellent choice when the fixture must be protected from dust, moisture, or vapor, yet still have the characteristics of a high efficiency luminaire. Totally enclosed and fully gasketed, the LED DVPE is a ideal fixture for outdoor locations, food and drug handling areas, locker/shower rooms, swimming pools, humid or cold storage, parking garages, and car washes. The LED DVPE body is a one piece, compression molded, reinforced polyester fiberglass housing. With lengths of 2, 4 & 8 feet, remote mounted sensors, reflector choices (including MIRO 4, anodized aluminum, and white) and multiple mounting options, the LED DVPE is very customizable to specific requirements.

Application

- Auditoriums
- Cafeterias / Hotels & Casinos
- Distribution Facilities
- Factories & Warehouses
- Convention Centers
- Aircraft Hangers
- Schools / Colleges / Universities
- Convenience Stores
- Correctional Facilities
- Government & Municipal
- Healthcare Facilities
- Hospitals
- Military Bases
- Museums / Libraries
- Office Buildings / Parking Garages
- Power Generation Facilities
- Repair & Service Centers
- Retail Locations / Supermarkets

Features and Benefits

- **Excellent for cold storage and damp locations** - With its polyester fiberglass housing and ballasts rated down to 0 °F / -18 °C, ideal for installation in cold storage, damp locations, and other locations not suitable for typical LED fixtures.
- **Decorative, glare reducing design** - Looks great in the ceiling and fixture glare is minimized.
- **No color shifting** - LED lamps maintain consistent and stable color throughout life.
- **Low Total Harmonic Distortion (THD)** - Decreased interference with infrared remote controlled electronics and other electronic appliances.
- **High color rendering index (CRI)** - Excellent and accurate color rendering.
- **Advanced computer specular reflector** - Extremely precise light focusing and distribution.

Certifications



Made in the USA

Specifications

MODEL#	OUTPUT	EFFICACY	WATTAGE	CCT	CRI	WARRANTY
OTLDVPE-L-4-2L-LIRA-RF-840-55W-3K	6924	86.96	79.24	4029	84	5 Years

OTLDVPE-L-DIRA-FORTIMO-840-55W-3K	7355	91.8	80.089	4026	83.4	5 Years
OTLDVPE-L-LIRA-FORTIMO-840-55W-3K	7894	80.135	98.5	4040	83	5 Years
OTLDVPE-L-4-2L-DIRA-UNVLT-840-M510C-255X2	8110	96.79	83.792	4110	82.76	5 Years
OTLDVPE-L-4-2L-LIRA-UNVLT-840-M510C-255X2	8710	103.82	83.892	4091	82.51	5 Years
OTLDVPE-L-4-2L-LIRA-RF-UNVLT-840-M510C-255X2	7648	91.36	83.717	4118	82.82	5 Years
OTLDVPE-L-4-2L-LIRA-RF-UNVLT-840-M510C-D310X1	5014	98.09	51.115	4082	82.77	5 Years
OTLDVPE-L-SMM-4-2L-DIRA-CC-FORTIMO-H-830-U	7529	101.3	74.34	3124	82.62	5 Years
OTLDVPE-L-SMM-4-2L-DIRA-CC-FORTIMO-H-840-U	7700	105	73	4000	83	5 Years
OTLDVPE-L-SMM-4-2L-DIRA-CC-FORTIMO-H-835-U	7600	103	73	3500	83	5 Years
OTLDVPE-L-SMM-4-2L-DIRA-CC-FORTIMO-H-850-U	7800	106	73	5000	83	5 Years
OTLDVPE-L-SMN-4-2L-DIRA-CC-UNVLT-H-830-U	6619	86.3	76.67	3088	83.72	5 Years
OTLDVPE-L-SMN-4-2L-DIRA-CC-UNVLT-H-840-U	7000	90	77	4000	82	5 Years
OTLDVPE-L-SMN-4-2L-DIRA-CC-UNVLT-H-850-U	7163	92.5	77.468	5000	84.4	5 Years
OTLDVPE-L-SMN-4-2L-DIRA-CC-UNVLT-H-835-U	6800	88	77	3500	82	5 Years
OTLDVPE-L-SMW-4-2L-DIRA-CC-OSRAM-L-835-U	5402	103.1	52.394	3468	82.95	5 Years
OTLDVPE-L-SMW-4-2L-DIRA-CC-OSRAM-L-850-U	5700	109	53	5000	82	5 Years
OTLDVPE-L-SMW-4-2L-DIRA-CC-OSRAM-L-840-U	5500	106	53	4000	82	5 Years
OTLDVPE-L-2-2L-PG-CC-UNVLT-H-830-U	3068	73.44	41.77	3070	84.06	5 Years
OTLDVPE-L-2-2L-PG-CC-UNVLT-H-840-U	3067.8	73.6	42	4000	86	5 Years
OTLDVPE-L-2-2L-PG-CC-UNVLT-H-835-U	3067.8	73.6	42	3500	85	5 Years
OTLDVPE-L-2-2L-PG-CC-UNVLT-H-850-U	3546	73.6	42.143	5000	88.85	5 Years

OnTimeLighting.com | 215.245.3400
47B Runway Road, Levittown, PA 19057